



POCKET 750 - POCKET 750MX



The perfect solution for high quality PA performance with minimum size and weight. The MX version features an onboard mixer which can be used both inside the subwoofer or remotely if required. A 2 pc padded case set is available for the 750 which makes transport

even more convenient and protects your investment. A set of high quality compact speaker stands for the satellite speakers are also available. The Pocket 750 is available in either Moquette or lacquered black finishes

Satellite Speaker

Frequency response 150Hz-20kHz
Sensitivity (1W-1m) 94 db
SPL max 118 db
Crossover Passive
System-format 2-way
Woofers 6"
Horn 1"
Nominal Impedance 4 ohm
Max Power Out 175 W RMS
Connections Speakon
Box Two-way bass reflex
Construction Plywood
Weight Kg 6
Dimensions (WxDxH) 21x25x33 cm

Subwoofer for 750

Frequency response 40-150 Hz
Sensitivity (1W-1m) 99 db
SPL max 126 db
Crossover Electronic -24db/octave
Woofers 12"
Max Power Out 400 W RMS ICEpower®
Line Inputs Left/Right XLR In + Link
MIC Input
Active Outputs 2 x Speakon OUT
Controls Bass Volume, High Volume, Ground Lift switch
Box Bass reflex
Construction Plywood
Weight Kg 19,5
Dimensions (WxDxH) 41x46,5x46 cm (16x18x18 inch)

Subwoofer for 750MX

Frequency response 40-150 Hz
Sensitivity (1W-1m) 99 db
SPL max 126 db
Crossover Electronic -24db/octave
Woofers 12"
Max Power Out 400 W RMS ICEpower®
Line Inputs Left/Right XLR In + Link; Mixer Remote Control
MIC Input
Active Outputs 2 x Speakon OUT
Controls Bass Volume, High Volume, Ground Lift switch
Box Bass reflex
Construction Plywood
Weight Kg 22,5
Dimensions (WxDxH) 41x46,5x46 cm (16x18x18 inch)

750MX Mixer Connections and Controls

2 mono channels XLR + Jack Gain, Hi, Mid, Low
1 stereo channel Jack Hi, Mid, Low
1 stereo line channel RCA Hi, Low
Internal effect 8 effects (by Alesis) Selector
Phantom power switch
Send & Ret. External effect Jack
Rec Out RCA Volume
Master Out XLR Volume
Construction: Steel case