



POCKET 1500 - POCKET 2100 - POCKET 4000



The perfect solution for high quality high output PA performance with the minimum of weight and cabling that allows ultra fast setup times. The basic 1500 system has inbuilt expansion allowing the addition of a second passive subwoofer to create

the Pocket 2100. Even greater output is available with the 4000 system that comprises 4 subwoofers and 2 SAT 700 cabinets to provide a total of 4200w RMS. All Pocket 1500 systems are available in a lacquered black finish

Satellite	SAT 350	SAT 700
Frequency response	120Hz-20kHz	120Hz-20kHz
Sensitivity (1W-1m)	97 dB	99,5 dB
SPL max	122 dB	128 dB
Crossover	Passive	Passive
System-format	2-way	2-way
Woofers	"8" neodimium Horn 1" neodimium	12" neodimium 2.4" neodimium
Coverage angle	90°x60°	60°x40°
Max Power Out	350 W RMS	700 W RMS
Nominal Impedance	4 ohm	8 ohm
Connections	Speakon In	Speakon In
Box	Two-way bass reflex	Two-way bass reflex
Construction	Plywood	Plywood
Weight	Kg 9	Kg 18,5
Dimensions WxDxH cm	25.5x30.5x41.5	38x39x67

Subwoofer Pocket	1500 BA (Active Bass)	Pocket 1500 BP (Passive Bass)
Frequency response	30-120Hz	30-120Hz
Sensitivity (1W-1m)	100 dB	100 dB
SPL max	129 dB	129 dB
Crossover Electronic - Woofers	24db/octave "15"	"15"
Max Power Out	800 W RMS	700 W RMS
Nominal Impedance		8 ohm
Active Outputs	L/R OUT; SW OUT	
Controls	Bass Volume, High Volume, Ground Lift	
switch,	Bass-SW switch	
Box	Bass reflex	Bass reflex
Construction	Plywood	Plywood
Weight	Kg 31	Kg 22
Dimensions WxDxH cm	45x66x45	45x66x45